



PNL Series LED

The PNL series is a compact, sleek, linear light offering evenly diffused lighting in a small form factor. Available in a single and double width, there are options for varying outputs and price points. The light features built-in receptacles for easy daisy chain, and optional built-in switch for task light applications.

FEATURES:

- 180 Degree Light Dispersion
- Single and double widths available
- Surface and magnet mount brackets
- Wire or end-to-end daisy chaining up to 200W
- Optional Triac dimming
- Optional on-off switch
- 3 Year Longevity


CONSTRUCTION:

- Impact resistant polycarbonate lens diffusion
- Corrosion resistant aluminum
- Aluminum circuit board for optimized LED lumen maintenance


SERIES SPECIFICATIONS:

- 100-240VAC for non-switched units
- 50/60 Hz
- THD<19%
- PF>95
- 1FT-8FT length available
- Full CCT options
- ETL listed to UL1598
- 12-24VDC available
- 6 foot power cord

5S



5D



STANDARD CONFIGURATION

Part Number	Length	Volts (AC)	Watts	Color (CCT) Standard	Switch	Delivered Lumens	CRI (Color Rendering Index)	Ambient Run & Storage Temperature
PNL5S-1-04W(S)	(1FT) 283mm 11 ^{3/16} "	120	4	5000K	Yes	400	80	-25°C to 50°C
PNL5D-4-40W(S)	(4FT) 1149mm 45 ^{1/4} "	120	40	5000K	Yes	4000	80	-25°C to 50°C

[Shop standard configurations](#) in our webstore or [contact us](#) directly for custom configurations

Disclaimer: Subject to minimums and price changes

Phone: 800-340-6842 | Web: www.RidgebackLighting.com | Email: sales@ridgebacklighting.com

Rev: March 2024